

SECTION 1: Product identifier

1.1. Product identifier

Product form : Mixture
Product name : Epoxy Thinner

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Thinning paint and cleaning paint guns. Used on Epoxy Paints.

1.4. Supplier's details

Manufacturer

Sydney Solvents Pty Ltd
3-10 Production Place
Jamisontown, NSW 2750
T 02 4722 5060 (office hours) - F 02 4722 5070
sales@sydney-solvents.com.au - www.sydney-solvents.com.au

1.5. Emergency phone number

Emergency number : Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)
Emergency Chemcall : 1800 127 406

SECTION 2: Hazards identification


2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 3	H226
Acute toxicity (oral), Category 4	H302
Acute toxicity (dermal), Category 3	H311
Acute toxicity (inhalation:vapour) Category 3	H331
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Carcinogenicity, Category 2	H351
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335
Aspiration hazard, Category 1	H304

2.2. Label elements

Hazard pictograms (GHS AU) :



Signal word (GHS AU) : Danger
Contains : Xylenes (o-, m-, p- isomers) (30 – 60 %); 2-Pentanone, 4-methyl- (30 – 60 %); 2-Butoxyethanol (30 – 60 %)
Hazard statements (GHS AU) : H226 - Flammable liquid and vapour
H302 - Harmful if swallowed
H304 - May be fatal if swallowed and enters airways

Epoxy Thinner

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

Precautionary statements (GHS AU)	<p>H311+H331 - Toxic in contact with skin or if inhaled H315 - Causes skin irritation H319 - Causes serious eye irritation H335 - May cause respiratory irritation H351 - Suspected of causing cancer</p> <p>: P201 - Obtain special instructions before use. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P240 - Ground and bond container and receiving equipment. P241 - Use explosion-proof equipment. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands, forearms and face thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P281 - Use personal protective equipment as required. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. P330 - Rinse mouth. P331 - Do NOT induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water . P332+P313 - If skin irritation occurs: Get medical advice/attention. P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P311 - Call a POISON CENTER or doctor. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.</p>
-----------------------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

Name	CAS-No.	%
Xylenes (o-, m-, p- isomers)	1330-20-7	40
2-Pentanone, 4-methyl-	108-10-1	30
2-Butoxyethanol	111-76-2	30

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER/doctor.
First-aid measures after skin contact	: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash clothing before re-using. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Epoxy Thinner

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person.

4.2. Symptoms caused by exposure

Symptoms/effects after inhalation : Toxic if inhaled. May cause irritation to the respiratory tract.
Symptoms/effects after skin contact : Toxic in contact with skin. Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion : Harmful if swallowed. May be fatal if swallowed and enters airways. May result in aspiration into the lungs, causing chemical pneumonia.
Chronic symptoms : Suspected of causing cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol resistant foam. carbon dioxide (CO2), dry chemical powder, water spray.
Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour. Products of combustion may include, and are not limited to: oxides of carbon. Toxic fumes. water. smokes.
Explosion hazard : May form flammable/explosive vapour-air mixture. Vapours are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapours. Vapours are heavier than air and can spread along the ground and collect in low or confined areas (sewers, basements, tanks).
General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges. Remove all sources of ignition.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool closed containers exposed to fire with water spray.
Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
Hazchem Code : * 3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric charges. Remove all sources of ignition.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

Epoxy Thinner

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so. Remove all sources of ignition. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not use sawdust or other combustible material to absorb spilled material. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not swallow. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Handle and open container with care.
- Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed.
- Storage conditions : Keep out of the reach of children. Store locked up. Keep in fireproof place. Store away from direct sunlight or other heat sources. Keep away from clothing and other combustible materials. Keep away from food, drink and animal feedingstuffs. Store tightly closed in a dry, cool and well-ventilated place.
- Storage temperature : < 30 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

Xylenes (o-, m-, p- isomers) (1330-20-7)	
Australia - Occupational Exposure Limits	
OES TWA [1]	350 mg/m ³
OES TWA [2]	80 ppm
OES STEL	655 mg/m ³
OES STEL [ppm]	150 ppm
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	100 ppm
ACGIH OEL STEL [ppm]	150 ppm
ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA - ACGIH - Biological Exposure Indices	
BEI	1.5 g/g creatinine Parameter: Methylhippuric acids - Medium: urine - Sampling time: end of shift
2-Pentanone, 4-methyl- (108-10-1)	
Australia - Occupational Exposure Limits	
OES TWA [1]	205 mg/m ³

Epoxy Thinner

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

2-Pentanone, 4-methyl- (108-10-1)	
OES TWA [2]	50 ppm
OES STEL	307 mg/m ³
OES STEL [ppm]	75 ppm
USA - ACGIH - Occupational Exposure Limits	
Local name	Methyl isobutyl ketone
ACGIH OEL TWA [ppm]	20 ppm
ACGIH OEL STEL [ppm]	75 ppm
Remark (ACGIH)	TLV® Basis: URT irr; dizziness; headache. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2021
USA - ACGIH - Biological Exposure Indices	
Local name	METHYL ISOBUTYL KETONE
BEI	1 mg/l Parameter: MIBK - Medium: urine - Sampling time: end of shift
Regulatory reference	ACGIH 2021
2-Butoxyethanol (111-76-2)	
Australia - Occupational Exposure Limits	
OES TWA [1]	96.9 mg/m ³
OES TWA [2]	20 ppm
OES STEL	242 mg/m ³
OES STEL [ppm]	50 ppm
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH OEL TWA [ppm]	20 ppm
Remark (ACGIH)	TLV® Basis: Eye & URT irr. Notations: A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans); BEI
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans
Regulatory reference	ACGIH 2020
USA - ACGIH - Biological Exposure Indices	
BEI	200 mg/g creatinine Parameter: Butoxyacetic acid with hydrolysis - Medium: urine - Sampling time: end of shift

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

8.4. Personal protective equipment

Materials for protective clothing : Polyvinylalcohol (PVA). Teflon. PE/EVAL.
Hand protection : Wear suitable gloves resistant to chemical penetration
Eye protection : Wear eye/face protection
Skin and body protection : Wear suitable protective clothing

Epoxy Thinner

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

Respiratory protection	: Wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Avoid release to the environment.
Other information	: Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

Physical state	: Liquid
Appearance	: Clear colourless liquid.
Colour	: Clear Colourless
Odour	: Characteristic
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point / Freezing point	: Liquid at normal temperatures
Boiling point	: 110 – 180 °C at 100kPa
Flash point	: 44 °C
Auto-ignition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapour.
Vapour pressure	: No data available
Relative density	: 0.864 (calculated)
Density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Explosive properties	: No data available
Explosive limits	: No data available
Minimum ignition energy	: No data available
Fat solubility	: No data available

SECTION 10: Stability and reactivity

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions. May form flammable/explosive vapour-air mixture.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Incompatible materials. Sources of ignition. Direct sunlight. Keep dry.
Incompatible materials	: Oxidizing agents.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. May release flammable gases. Toxic fumes. water. smokes.

SECTION 11: Toxicological information

Acute toxicity (oral)	: Harmful if swallowed.
Acute toxicity (dermal)	: Toxic in contact with skin.
Acute toxicity (inhalation)	: Toxic if inhaled.

ATE AU (oral)	1115.058 mg/kg bodyweight
ATE AU (dermal)	975.658 mg/kg bodyweight
ATE AU (vapours)	5.228 mg/l/4h

Xylenes (o-, m-, p- isomers) (1330-20-7)

LD50 oral rat	3500 mg/kg
LD50 dermal	1700 mg/kg

2-Pentanone, 4-methyl- (108-10-1)

LD50 oral rat	2080 mg/kg
LD50 dermal rabbit	3000 mg/kg

Epoxy Thinner

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

2-Pentanone, 4-methyl- (108-10-1)	
LC50 inhalation rat	11.6 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
LC50 inhalation rat	2000 – 4000 ppm/4h
2-Butoxyethanol (111-76-2)	
LD50 oral rat	470 mg/kg
LD50 oral	1414 mg/kg bodyweight Animal: guinea pig, Guideline: OECD Guideline 401 (Acute Oral Toxicity), 95% CL: 1020 - 1961
LD50 dermal rabbit	435 mg/kg
LC50 inhalation rat	2.35 mg/l
LC50 inhalation rat	486 ppm/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: Not classified.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified.
STOT-single exposure	: May cause respiratory irritation.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
STOT-single exposure	May cause respiratory irritation.
2-Pentanone, 4-methyl- (108-10-1)	
STOT-single exposure	May cause respiratory irritation.
STOT-repeated exposure	: Not classified.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
LOAEL (oral, rat, 90 days)	150 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents), Guideline: EPA OPP 82-1 (90-Day Oral Toxicity)
2-Pentanone, 4-methyl- (108-10-1)	
LOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEL (oral, rat, 90 days)	250 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	4.106 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
2-Butoxyethanol (111-76-2)	
NOAEL (dermal, rat/rabbit, 90 days)	> 150 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard : May be fatal if swallowed and enters airways.
Other information : Likely routes of exposure: ingestion, inhalation, skin and eye

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

12.1. Ecotoxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, long-term (chronic) : Not classified.

Epoxy Thinner

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

Other information : No other effects known.

Xylenes (o-, m-, p- isomers) (1330-20-7)	
LC50 - Fish [1]	2.6 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)
LC50 - Fish [2]	2.661 – 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 - Crustacea [1]	> 3.4 mg/l Test organisms (species): Ceriodaphnia dubia
EC50 - Crustacea [2]	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)
LOEC (chronic)	3.16 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 1.3 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri) Duration: '56 d'
BCF - Fish [1]	0.6 – 15
Partition coefficient n-octanol/water	2.77 – 3.15
2-Pentanone, 4-methyl- (108-10-1)	
LC50 - Fish [1]	505 mg/l
EC50 - Crustacea [1]	1250 mg/l
NOEC chronic fish	57 mg/l
NOEC chronic crustacea	7.8 mg/l
Partition coefficient n-octanol/water	1.19
2-Butoxyethanol (111-76-2)	
LC50 - Fish [1]	1490 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 - Fish [2]	2950 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)
EC50 - Crustacea [1]	> 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna)
NOEC (chronic)	100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'
NOEC chronic fish	> 100 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio) Duration: '21 d'
Partition coefficient n-octanol/water	0.81 (at 25 °C)
12.2. Persistence and degradability	
Epoxy Thinner	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
Epoxy Thinner	
Bioaccumulative potential	Not established.
Xylenes (o-, m-, p- isomers) (1330-20-7)	
BCF - Fish [1]	0.6 – 15
Partition coefficient n-octanol/water	2.77 – 3.15
2-Pentanone, 4-methyl- (108-10-1)	
Partition coefficient n-octanol/water	1.19
2-Butoxyethanol (111-76-2)	
Partition coefficient n-octanol/water	0.81 (at 25 °C)

Epoxy Thinner

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

12.4. Mobility in soil

Xylenes (o-, m-, p- isomers) (1330-20-7)

Partition coefficient n-octanol/water : 2.77 – 3.15

2-Pentanone, 4-methyl- (108-10-1)

Partition coefficient n-octanol/water : 1.19

2-Butoxyethanol (111-76-2)

Partition coefficient n-octanol/water : 0.81 (at 25 °C)

12.5. Other adverse effects

Ozone : Not classified.

Other adverse effects : No additional information available

Epoxy Thinner

Fluorinated greenhouse gases : False

Xylenes (o-, m-, p- isomers) (1330-20-7)

Fluorinated greenhouse gases : False

2-Pentanone, 4-methyl- (108-10-1)

Fluorinated greenhouse gases : False

2-Butoxyethanol (111-76-2)

Fluorinated greenhouse gases : False

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimized wherever possible. Recycle empty containers where allowed.

Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1993

UN-No. (IMDG) : 1993

UN-No. (IATA) : 1993

14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG) : FLAMMABLE LIQUID, N.O.S. (Xylenes (o-, m-, p- isomers) ; 4-methyl-2-Pentanone)

Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S. (Xylenes (o-, m-, p- isomers) ; 4-methyl-2-Pentanone)

Proper Shipping Name (IATA) : Flammable liquid, n.o.s. (Xylenes (o-, m-, p- isomers) ; 4-methyl-2-Pentanone)

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 3

Danger labels (ADG) : 3



Epoxy Thinner

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3
:



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3
:



14.4. Packing group

Packing group (ADG) : II - substances presenting medium danger
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Marine pollutant : No
Dangerous for the environment : No
Other information : No supplementary information available.

14.6. Special precautions for user

Specific storage requirement : No data available
Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available.
Special transport precautions : Do not handle until all safety precautions have been read and understood.

Transport by road and rail

UN-No. (ADG) : 1993
Special provision (ADG) : 274
Limited quantities (ADG) : 1I
Packing instructions (ADG) : P001, IBC02
Portable tank and bulk container instructions (ADG) : T7
Portable tank and bulk container special provisions (ADG) : TP1, TP8, TP28

Transport by sea

UN-No. (IMDG) : 1993

Air transport

UN-No. (IATA) : 1993

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

Epoxy Thinner

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 24/08/2021
Expiry date : 24/08/2026
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Classification	
Flam. Liq. 3	H226
Acute Tox. 4 (Oral)	H302
Acute Tox. 3 (Dermal)	H311
Acute Tox. 3 (Inhalation:vapour)	H331
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Carc. 2	H351
STOT SE 3	H335
Asp. Tox. 1	H304

Safety Data Sheet (SDS), Australia - Nexreg 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.