

.

. .

1 40

#### FOR FURTHER INFORMATION, PLEASE REFER TO THE SDS

		Issue: March 19	
PRODUCT:	lsopar™ G (B)	UN No.	3295
Other Names:	Isoparaffins	Dangerous Goods Class	3
		Subsidiary Risk	None
Uses:	Industrial solvent: plastics manufacture, cleaning	Pack Group	III
	chemicals	Hazchem	3Y
		Poison Schedule	5

Hazardous Nature:	This product is classified as hazardous under Australian GHS criteria				
Hazardous Categories:	Flammable Liquids: 3; Aspiration Toxicant: 1; Skin Corrosion/Irritation: 3; Chronic				
	Aquatic Toxicant: 2				
Exposure Standards:	TWA: 1200 mg/m <sup>3</sup> (196 ppm): STEL: None specified; consider 5 g/m <sup>3</sup>				
Physical Characteristics (Typical)			Section 9 of SDS		
Appearance		Clear, colourless liqui	d		
Boiling Point/ Range (°C):		153 - 180			
Flash Point (°C):		> 40			
Specific Gravity/ Density (g/ml @ 15°C):		0.75			
Chemical Stability:		Stable at room tempe	rature and pressure		
Product Ingredients			Section 3 of SDS		
Naphth (Petroleum), Hydrotreated Heavy		64742-48-9	100		
Contains: nonane		111-84-2	< 5		
Note: contains < 0.01% benzen	e				

For further ingredients information, please refer to the full SDS.

GHS Pictograms		Section 2 of SDS
		¥2
Hazard Statements		Section 2 of SDS
UDDC. Flammable liquid		

H226: Flammable liquid and vapour

H304: May be fatal if swallowed and enters airways

H316: Causes mild skin irritation

H411: Toxic to aquatic life with long lasting effects

For further Risk and Safety information, please refer to the full SDS.

#### DEFINITIONS

DEFINITIONS				
Dangerous Goods	Products that are classified as Dangerous for Storage and Transport: these products are allocated a UN No., with accompanying Class, Pack Group, and Sub. Risk, if required. Products that do not have a specific description under the code, but have low flash points, or such, must be classified under their most significant risk, eg. Flammable Goods N.O.S. (Not otherwise specified), UN 1993			
Poisonous Substance	Products that are classified under the poisons schedule are a poisonous substance. The proportion of the poison in the product will determine its numerical classification.			
Hazardous Substance	Products are considered to be Hazardous if they pose an intrinsic risk to human or environmental health, such as mutagens (able to change DNA), teratogens (able to result in birth defects), carcinogens (able to generate cell abnormalities), etc. Materials are not hazardous substances if they pose risks such as potential for misuse, like flammability, or explosions when heated and ignited.			

# 1. IDENTIFICATION

Product Name:	lsopar™ G (B)			
Other Names:	Isoparaffins			
Chemical Family:	Isoparaffinic hydrocarbon			
Recommended Use:	Industrial solvent: plastics manufacture, cleaning chemicals			
Supplier:	Sydney Solvents Pty Ltd			
ABN:	51 104 642 695			
Street Address:	Unit 3, 10 Production Place, Jamisontown NSW 2750			
Telephone:	(02) 4722 5060			
Emergency phone:	CHEMCALL: 1800 127 406			

# 2. HAZARDS IDENTIFICATION

#### **Health Hazard Classification**

This product is classified as hazardous under Australian GHS criteria

#### Hazard Categories

Flammable Liquids: 3; Aspiration Toxicant: 1; Skin Corrosion/Irritation: 3; Chronic Aquatic Toxicant: 2

#### Hazardous Statement

Flammable Liquid and Vapour

#### **GHS** Pictograms



#### Hazard Statements

H226: Flammable liquid and vapour

H304: May be fatal if swallowed and enters airways

H316: Causes mild skin irritation

H411: Toxic to aquatic life with long lasting effects

#### **Precautionary Statements**

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P262: Do not get in eyes, on skin, or on clothing.

P243: Take precautionary measures against static discharge.

P378: Use sand, earth, or chemical foam to extinguish.

P301+312+101: IF SWALLOWED: Call a POISON CENTER/doctor, if you feel unwell, and have product container or label at hand.

#### **Dangerous Goods Classification** 3

#### Poisons Schedule 5

Signal Word Danger

# Safety Data Sheet

# Composition: Information on Ingredients Chemical Ingredient CAS No. Proportion (%v/v) Naphth (Petroleum), Hydrotreated 64742-48-9 100 Heavy 111-84-2 < 5</td> Note: contains < 0.01% benzene</td>

# 4. FIRST AID MEASURES

#### For advice, contact Poisons Information Centre (Phone Australia: 13 1126) or a doctor.

#### Ingestion

If swallowed, DO NOT induce vomiting. Keep at rest. Seek immediate medical attention.

#### Eye Contact

Flush eyes with large amounts of water until irritation subsides. Seek immediate medical attention.

#### Skin Contact

Flush area with large amounts of water and wash area with soap if available. Remove contaminated clothing, including shoes, and launder before reuse. Seek medical attention for skin irritations.

#### **Inhalation**

Using proper respiratory protection, immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Seek immediate medical attention.

#### **First Aid facilities**

Provide eye baths and safety showers.

#### **Medical Attention**

Treat according to symptoms. Avoid gastric lavage: risk of aspiration of product to the lungs with the potential to cause chemical pneumonitis.

# 5. FIRE FIGHTING MEASURES

Shut off product that may 'fuel' a fire if safe to do so. Allow trained personnel to attend a fire in progress, providing firefighters with this Material Safety Data Sheet. Prevent extinguishing media from escaping to drains and waterways.

#### Suitable extinguishing media

Dry chemical or foam

#### Hazards from combustion products

Carbon dioxide and carbon monoxide

#### Precautions for fire fighters and special protective equipment

Full protective clothing and self-contained breathing apparatus

#### Hazchem Code:

3Y

# 6. ACCIDENTAL RELEASE MEASURES

## **Emergency Procedures**

Prevent fluid from escaping to drains and waterways. Contain leaking packaging in a containment drum. Prevent vapours from building up in confined areas. Ensure that drain valves are closed at all times. Clean up and report spills immediately.

# Methods and materials for containment

# Major Land Spill

- Eliminate sources of ignition.
- Warn occupants of downwind areas of possible fire and explosion hazard.
- Prevent liquid from entering sewers, watercourses, or low-lying areas.
- Keep the public away from the area.
- Shut off the source of the spill if possible and safe to do so.

# ISOPAR™ G (B)

- Advise authorities if substance has entered a watercourse or sewer or has contaminated soil or vegetation.
- Take measures to minimise the effect on the ground water.
- Contain the spilled liquid with sand or earth.
- Recover by pumping use explosion proof pump or hand pump or with a suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See "First Aid Measures" and "Stability and Reactivity"

#### Major Water Spill

- Eliminate any sources of ignition.
- Warn occupants and shipping in downwind areas of possible fire and explosion hazard.
- Notify the port or relevant authority and keep the public away from the area.
- Shut off the source of the spill if possible and safe to do so.
- Confine the spill if possible.
- Remove the product from the surface by skimming or with suitable absorbent material.
- Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.
- See "First Aid Measures" and "Stability and Reactivity".

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

This product is flammable. Do not open near open flame, sources of heat or ignition. No smoking. Keep container closed. Handle containers with care. Open slowly to control possible pressure release. Material will accumulate static charge. Use grounding leads to avoid discharge (electrical spark).

#### **Conditions for safe storage**

Store in a cool, dry place away from direct sunlight. Do not pressurise, cut, heat or weld containers - residual vapours are flammable. This product is flammable and will fuel a fire in progress.

#### Incompatible materials

Natural Rubber, Butyl Rubber, EPDM, Polystyrene

# 8. EXPOSURE CONTROLS: PERSONAL PROTECTION

#### **National Exposure Standards**

The time weighted average concentration (TWA) for this product is: 1200 mg/m3 (196 ppm), which means the highest allowable exposure concentration in an eight-hour day for a five-day working week. The short-term exposure limit (STEL) is: None specified; consider 5 g/m3, which is the maximum allowable exposure concentration at any time.

#### **Biological limit values**

Not available

#### Engineering Controls: Ventilation

The use of local exhaust ventilation is recommended to control process emissions near the source. Laboratory samples should be handled in a fume hood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

#### Personal Protective Equipment

**Respiratory Protection:** Where concentrations in air may exceed the limits described in the National Exposure Standards, it is recommended to use a half-face filter mask to protect from overexposure by inhalation. A type "A" filter material is considered suitable for this product.

Eye Protection: Always use safety glasses or a face shield when handling this product.

**Skin/ Body Protection:** Always wear long sleeves and long trousers or coveralls, and enclosed footwear or safety boots when handling this product. It is recommended that chemical resistant gloves (e.g. PVC) be worn when handling this product.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value	
Appearance	-	Clear, colourless liquid	

# Safety Data Sheet

Property	Unit of measurement	Typical value	
Boiling Point/ Range	°C	153 - 180	
Flash Point	°C	> 40	
Density @ 15°C	g/ml	0.75	
Vapour Pressure @ 20°C	kPa	0.195	
Explosive Limits (LEL – UEL)	%	0.7 – 5.6	
Vapour Density @ 20°C	kPa	5.03	
Autoignition Temperature	°C	365	
Viscosity @ 25°C	cSt	1.49	
Percent Volatiles	%	100	
Solubility with Water	% w/w	< 0.10	

The values listed are indicative of this product's physical and chemical properties. For a full product specification, please consult the Product Data Sheet.

# **10.STABILITY AND REACTIVITY**

#### **Chemical Stability**

Stable at room temperature and pressure

#### **Conditions to avoid**

Sources of heat and ignition, open flames.

#### Hazardous decomposition products

Carbon monoxide, carbon dioxide, and other organic complexes on incomplete burning or oxidation

#### Hazardous reactions

Oxidizing agents, mineral acids, halogenated organic compounds

#### Hazardous Polymerisation

Will not occur

# 11.TOXICOLOGICAL INFORMATION

#### **Acute Effects**

#### Ingestion

Small amounts of liquid aspirated into the lungs during ingestion, or from vomiting, may cause chemical pneumonitis, or pulmonary oedema. Ingesting large amounts of this product will result in headaches, nausea, dizziness, and tracheal burning.

#### Eye Contact

This product is irritating to eyes, but will not permanently damage the eye tissue

#### Skin Contact

This product is irritating to the skin with prolonged exposure. It may result in dryness and cracking.

#### Inhalation

Inhalation of this product will yield moderate discomfort in large quantities. Vapour concentrations are irritating to nose and throat. Overexposure may be evident through dizziness, nausea, headaches and other central nervous system effects.

#### Chronic Effects

No chronic health data is available for this product.

#### **Other Health Effects Information**

May cause drowsiness or dizziness.

#### **Toxicological Information**

Oral LD<sub>50</sub>: LD<sub>50</sub> > 10000 mg/kg Dermal TC<sub>L0</sub>: LC<sub>50</sub> > 5000 mg/m<sup>3</sup>

#### **Ecotoxicity**

#### **Aquatic Toxicity**

Fish Toxicity (rainbow trout, goldfish, bluegill):

Daphnia Magna EC<sub>50</sub> (24 hr): Blue-green algae (Toxicity threshold 7-8 days): Green algae (Toxicity threshold 7-8 days):

#### Persistence/ degradability

This product will evaporate and commence degradation on exposure to light and air.

#### Mobility

This product is highly volatile and will rapidly evaporate to the air if released into the water

#### **13.DISPOSAL CONSIDERATIONS**

#### **Disposal Methods**

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national and local authorities. Packaging may still contain fumes and vapours that are flammable and harmful. Ensure that empty packaging is allowed to dry.

organisms.

Not available

Not available

Not available

#### **Special Precautions for Landfill or Incineration**

This product is NOT suitable for disposal by either landfill or via municipal sewers, drains, natural streams or rivers. This product is ashless and can be burned directly in appropriate equipment.

# **14.TRANSPORT INFORMATION**

Road and Rail Transport		Marine Transport		Air Transport	
UN No.	3295	UN No.	3295	UN No.	3295
Proper Shipping Name	Liquid Hydrocarbons, N.O.S.	Proper Shipping Name	Liquid Hydrocarbons, N.O.S.	Proper Shipping Name	Liquid Hydrocarbons, N.O.S.
DG Class	3	DG Class	3	DG Class	3
Sub. Risk	None	Sub. Risk	None	Sub. Risk	None
Pack Group		Pack Group		Pack Group	III
Hazchem	ЗҮ	Hazchem	ЗҮ	Hazchem	ЗҮ

#### **Dangerous Goods Segregation**

This product is classed as Dangerous Goods Class 3, packing group III. Please consult the Australian Dangerous Goods Code for Transport by Road and Rail for information.

#### Marpol 73/78 Convention – Annex II

Product Name: NOXIOUS LIQUID, N.F.,(7) N.O.S., (ISOPAR G, contains iso-and cycloalkanes (C10-C11)) Ship Type: 3

Pollution: Y

## **15.REGULATORY INFORMATION**

Country/ Region: Australia Inventory: AICS Status: Listed Poisons Schedule: 5  $LC_{50}(96hr)$ : Based on data for a similar component or preparation, this product is expected to be toxic to aquatic

# **16.OTHER INFORMATION**

Reasons for Issue: Section 2: corrected skin irritation statement.

#### Abbreviations:

AICS: Australian Inventory of Chemical Substances CAS Number: Chemical Abstracts Number IARC: International Agency for Research on Cancer NOHSC: National Occupational Health and Safety Council GHS: Global Harmonised System

#### **References:**

- Supplier Material Safety Data Sheets
- <u>http://chem.sis.nlm.nih.gov/chemidplus</u> (March 19)
- <u>http://hsis.ascc.gov.au/SearchHS.aspx</u> (March 19)
- Ecotoxicology data: <u>http://cfpub.epa.gov/ecotox/quick\_query.htm</u> (March 19)
- Sax's Dangerous Properties of Industrial Materials, Richard J. Lewis Snr., pub. Canada (2000)

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses, but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact Australasian Solvents and Chemicals Company Pty. Ltd.