

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021 Issue date: 10/29/2021 Revision date: 10/29/2021 Version: 1.0

SECTION 1: Product identifier

1.1. Product identifier

Product form : Mixture

Product name Throttle Body Cleaner

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Industrial solvent, throttle body and carby cleaner

1.4. Supplier's details

Manufacturer

Sydney Solvents Pty Ltd 3-10 Production Place Jamisontown, NSW 2750

T 02 4722 5060 (office hours) - F 02 4722 5070

sales@sydneysolvents.com.au - www.sydneysolvents.com.au

1.5. Emergency phone number

Emergency number : Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New

Zealand)

: 1800 127 406 **Emergency Chemcall**

SECTION 2: Hazards identification

2.1. Classification of the hazardous chemical

Classification according to the model Work Health and Safety Regulations (WHS Regulations)

Flammable liquids, Category 2	H225
Acute toxicity (oral), Category 4	H302
Acute toxicity (dermal), Category 4	H312
Acute toxicity (inhalation:vapour) Category 4	H332
Skin corrosion/irritation, Category 2	H315
Serious eye damage/eye irritation, Category 2A	H319
Reproductive toxicity, Category 1A	H360
Specific target organ toxicity — single exposure, Category 1	H370
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336
Specific target organ toxicity — Repeated exposure, Category 2	H373
Aspiration hazard, Category 1	H304

2.2. Label elements

Hazard pictograms (GHS AU)



GHS02 Flame



GHS07 Exclamation mark



GHS08 Health hazard

Signal word (GHS AU)

: Danger

Contains : Toluene (30 - 60 %); Acetone (30 - 60 %); Methanol (10 - 30 %)

Hazard statements (GHS AU) : H225 - Highly flammable liquid and vapour

H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled

Safety Data Sheet

Precautionary statements (GHS AU)

according to the Model Work Health and Safety Regulations dated January 1, 2021

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H360 - May damage fertility or the unborn child

H370 - Causes damage to organs

H373 - May cause damage to organs through prolonged or repeated exposure

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof equipment.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P281 - Use personal protective equipment as required.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P331 - Do NOT induce vomiting.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P363 - Wash contaminated clothing before reuse.

P332+P313 - If skin irritation occurs: Get medical advice/attention.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 - Call a POISON CENTER or doctor if you feel unwell.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 - If eye irritation persists: Get medical advice/attention.

P307+P311 - IF exposed: Call a POISON CENTER or doctor/physician.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

Name	CAS-No.	%
Toluene	108-88-3	30 – 60
Acetone	67-64-1	30 – 60
Methanol	67-56-1	10 – 30

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation

: IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER/doctor if you feel unwell.

First-aid measures after skin contact

: If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.

10/29/2021 (Revision date) EN (English) 2/11

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

First-aid measures after ingestion : IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

Never give anything by mouth to an unconscious person.

4.2. Symptoms caused by exposure

Symptoms/effects : Causes damage to organs.

Symptoms/effects after inhalation : Harmful if inhaled. May cause irritation to the respiratory tract. May cause drowsiness or

dizziness.

Symptoms/effects after skin contact : Harmful in contact with skin. Causes skin irritation. Symptoms may include redness, edema,

drying, defatting and cracking of the skin.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking

and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. May result in aspiration into the lungs,

causing chemical pneumonia. May cause gastrointestinal irritation, nausea, vomiting and diarrhea. This material contains methanol, which, when ingested, may cause acidosis, ocular toxicity ranging from diminished visual capacity to complete blindness, and death.

: May damage fertility or the unborn child. May cause damage to organs through prolonged

or repeated exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice

immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Chronic symptoms

Suitable extinguishing media : Alcohol resistant foam. Water spray, fog or mist.

Unsuitable extinguishing media : Do not use water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour. Products of combustion may include, and are not

limited to: oxides of carbon. Organic compounds.

Explosion hazard : May form flammable/explosive vapour-air mixture. Vapours are heavier than air and may

travel considerable distance to an ignition source and flash back to source of vapours.

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry

to unnecessary and unprotected personnel. Use special care to avoid static electric

charges. Remove all sources of ignition.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool closed

containers exposed to fire with water spray.

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA).

Hazchem Code : * 3YE

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Use special care to avoid static electric

charges. Remove all sources of ignition.

6.1.1. For non-emergency personnel

No additional information available

10/29/2021 (Revision date) EN (English) 3/11

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Remove all sources of ignition. Absorb and/or contain spill with

inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal

protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed Precautions for safe handling

: Handle empty containers with care because residual vapours are flammable.

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharge. Use only explosion-proof equipment. Use only non-sparking tools. Do not get in eyes, on skin, or on clothing. Do not breathe dust/fume/gas/mist/vapours/spray. Do not swallow. When using do not eat, drink or smoke.

Handle and open container with care.

Hygiene measures : Take off immediately all contaminated clothing and wash it before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands, forearms and face

thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed.

Storage conditions

: Keep out of the reach of children. Store locked up. Keep in fireproof place. Keep away from heat and direct sunlight. Keep away from clothing and other combustible materials. Keep away from food, drink and animal feedingstuffs. Store tightly closed in a dry, cool and well-

ventilated place.

Incompatible materials : Natural rubber. Butyl rubber. Ethylene-Propylene rubber (EPDM). Polystyrene.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters - exposure standards

Toluene (108-88-3)		
Australia - Occupational Exposure Limits		
OES TWA [1]	191 mg/m³	
OES TWA [2]	50 ppm	
OES STEL	574 mg/m³	
OES STEL [ppm]	150 ppm	
USA - ACGIH - Occupational Exposure Limits		
Local name	Toluene	
ACGIH OEL TWA [ppm]	20 ppm	
Remark (ACGIH)	TLV® Basis: Visual impair; female repro; pregnancy loss. Notations: A4 (Not classifiable as a Human Carcinogen); BEI	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

Toluene (108-88-3)		
Regulatory reference	ACGIH 2020	
USA - ACGIH - Biological Exposure Indices		
BEI	0.02 mg/l Parameter: Toluene - Medium: blood - Sampling time: prior to last shift of workweek 0.03 mg/l Parameter: Toluene - Medium: urine - Sampling time: end of shift 0.3 mg/g creatinine Parameter: o-Cresol with hydrolysis - Medium: urine - Sampling time: end of shift (background)	
Acetone (67-64-1)		
Australia - Occupational Exposure Limits		
OES TWA [1]	1185 mg/m³	
OES TWA [2]	500 ppm	
OES STEL	2375 mg/m³	
OES STEL [ppm]	1000 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	250 ppm	
ACGIH OEL STEL [ppm]	500 ppm	
ACGIH chemical category	Not Classifiable as a Human Carcinogen	
USA - ACGIH - Biological Exposure Indices		
BEI	25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift (nonspecific)	
Methanol (67-56-1)		
Australia - Occupational Exposure Limits		
OES TWA [1]	262 mg/m³	
OES TWA [2]	200 ppm	
OES STEL	328 mg/m³	
OES STEL [ppm]	250 ppm	
USA - ACGIH - Occupational Exposure Limits		
ACGIH OEL TWA [ppm]	200 ppm	
ACGIH OEL STEL [ppm]	250 ppm	
ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route	
USA - ACGIH - Biological Exposure Indices		
BEI	15 mg/l Parameter: Methanol - Medium: urine - Sampling time: end of shift (background, nonspecific)	

8.2. Monitoring

No additional information available

8.3. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations

and safety showers.

8.4. Personal protective equipment

Hand protection : Wear suitable gloves resistant to chemical penetration

Eye protection : Wear eye/face protection
Skin and body protection : Wear suitable protective clothing

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

Respiratory protection : Wear suitable respiratory equipment. Respirator selection must be based on known or

anticipated exposure levels, the hazards of the product and the safe working limits of the

selected respirator.

Environmental exposure controls : Avoid release to the environment.

Other information : Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink

or smoke when using this product.

SECTION 9: Physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Colour : Clear
Odour : Solvent

Odour threshold : No data available

pH : 7

Relative evaporation rate (butylacetate=1) : No data available Melting point / Freezing point : No data available Boiling point : $56-110\,^{\circ}\text{C}$ Flash point : $-2\,^{\circ}\text{C}$

Auto-ignition temperature : No data available Flammability (solid, gas) : Not flammable Vapour pressure : No data available Relative density : No data available

Density: 0.82 g/ml (@ 15 °C)

Solubility : Miscible with water.

Partition coefficient n-octanol/water : No data available

Explosive properties : No data available

Explosive limits : No data available

Minimum ignition energy : No data available

VOC content : 100 %

Fat solubility : No data available

SECTION 10: Stability and reactivity

Reactivity : No dangerous reactions known under normal conditions of use.

Chemical stability : Stable under normal conditions. May form flammable/explosive vapour-air mixture.

Possibility of hazardous reactions : No dangerous reactions known under normal conditions of use.

Conditions to avoid : Heat. Incompatible materials. Sources of ignition. Direct sunlight.

Incompatible materials : Oxidizing agents. Mineral acids. Halogenated compounds. Peroxides. Natural rubber. Butyl

rubber. Ethylene-Propylene rubber (EPDM). Polystyrene.

Hazardous decomposition products : May include, and are not limited to: oxides of carbon. Organic compounds. May release

flammable gases.

12000 mg/kg

SECTION 11: Toxicological information

LD50 dermal rabbit

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Harmful in contact with skin.

Acute toxicity (inhalation) : Harmful if inhaled

Acute toxicity (initialation)	Harrillur II IIIInaleu.
ATE AU (oral)	464.286 mg/kg bodyweight
ATE AU (dermal)	1500 mg/kg bodyweight
ATE AU (vapours)	10.135 mg/l/4h
Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 oral	5000 mg/kg

10/29/2021 (Revision date) EN (English) 6/11

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

Toluene (108-88-3)	
LC50 inhalation rat	12.5 mg/l/4h
Acetone (67-64-1)	
LD50 oral rat	5800 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 15700 mg/kg
LC50 inhalation rat	76 mg/l air Animal: rat, Animal sex: female, 95% CL: 65,2 - 88,4
Methanol (67-56-1)	
LD50 oral rat	1187 – 2769 mg/kg bodyweight Animal: rat
LD50 dermal rabbit	15840 mg/kg
LC50 inhalation rat	22500 ppm (Exposure time: 8 h)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	pH: 7 : Causes serious eye irritation. pH: 7
Respiratory or skin sensitisation Germ cell mutagenicity Carcinogenicity	: Not classified.: Not classified.: Not classified.
Reproductive toxicity STOT-single exposure	: May damage fertility or the unborn child.: Causes damage to organs. May cause drowsiness or dizziness.
Toluene (108-88-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Acetone (67-64-1)	
STOT-single exposure	May cause drowsiness or dizziness.
Methanol (67-56-1)	
STOT-single exposure	Causes damage to organs.
STOT-repeated exposure	: May cause damage to organs through prolonged or repeated exposure.
Toluene (108-88-3)	
LOAEL (oral, rat, 90 days)	1250 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral, rat, 90 days)	625 mg/kg bodyweight Animal: rat, Guideline: EU Method B.26 (Sub-Chronic Oral Toxicity Test: Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEC (inhalation, rat, vapour, 90 days)	2.355 mg/l air Animal: rat, Guideline: EU Method B.29 (Sub-Chronic Inhalation Toxicity:90 Day Study)
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard Other information	May be fatal if swallowed and enters airways. Likely routes of exposure: ingestion, inhalation, skin and eye

SECTION 12: Ecological information

According to the National Code of Practice for the Preparation of Material Safety Data Sheets, Environmental classification information is not mandatory. Information relevant for GHS classification is available on request

: Not classified.

12.1. Ecotoxicity

Ecology - general

: May cause long-term adverse effects in the aquatic environment.

 $\label{thm:long-term} \mbox{Hazardous to the aquatic environment, long-term}$

(chronic)

Other information : No other effects known.

10/29/2021 (Revision date) EN (English) 7/11

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

Toluene (108-88-3)		
LC50 - Fish [1]	5.5 mg/l Test organisms (species): Oncorhynchus kisutch	
LC50 - Fish [2]	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 - Crustacea [1]	5.46 – 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
EC50 - Crustacea [2]	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LOEC (chronic)	2.76 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
NOEC (chronic)	0.74 mg/l Test organisms (species): Ceriodaphnia dubia Duration: '7 d'	
NOEC chronic fish	1.39 mg/l Test organisms (species): Oncorhynchus kisutch Duration: '40 d'	
NOEC chronic crustacea	0.74 mg/l	
Partition coefficient n-octanol/water	2.7	
Acetone (67-64-1)		
LC50 - Fish [1]	4.74 – 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)	
LC50 - Fish [2]	6210 – 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
EC50 - Crustacea [1]	10294 – 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
EC50 - Crustacea [2]	12600 – 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
LOEC (chronic)	> 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
NOEC (chronic)	≥ 79 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
BCF - Fish [1]	0.69	
Partition coefficient n-octanol/water	-0.24	
Methanol (67-56-1)		
LC50 - Fish [1]	15400 mg/l Test organisms (species): Lepomis macrochirus	
LC50 - Fish [2]	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])	
NOEC (chronic)	208 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
BCF - Fish [1]	< 10	
Partition coefficient n-octanol/water	-0.77	

12.2. Persistence and degradability

Throttle Body Cleaner	
Persistence and degradability	Readily biodegradable. Oxidises rapidly by photo-chemical reactions in air. Does not bioaccumulate significantly.
Acetone (67-64-1)	
Not rapidly degradable	

12.3. Bioaccumulative potential

Throttle Body Cleaner	
Bioaccumulative potential	Not established.
Toluene (108-88-3)	
Partition coefficient n-octanol/water	2.7
Acetone (67-64-1)	
BCF - Fish [1]	0.69
Partition coefficient n-octanol/water	-0.24

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

Methanol (67-56-1)	
BCF - Fish [1]	< 10
Partition coefficient n-octanol/water	-0.77

12.4. Mobility in soil

Throttle Body Cleaner		
Ecology - soil	Very mobile.	
Toluene (108-88-3)		
Partition coefficient n-octanol/water	2.7	
Acetone (67-64-1)		
Partition coefficient n-octanol/water	-0.24	
Methanol (67-56-1)		
Partition coefficient n-octanol/water	-0.77	

12.5. Other adverse effects

Ozone : Not classified.

Other adverse effects : No additional information available

Other adverse effects .	NO additional information available	
Throttle Body Cleaner		
Fluorinated greenhouse gases	False	
Toluene (108-88-3)		
Fluorinated greenhouse gases	False	
Acetone (67-64-1)		
Fluorinated greenhouse gases	False	
Methanol (67-56-1)		
Fluorinated greenhouse gases	False	

SECTION 13: Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance

with local, regional, national and/or international regulation. The generation of waste should

be avoided or minimized wherever possible.

Additional information : Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

14.1. UN number

UN-No. (ADG) : 1993 UN-No. (IMDG) : 1993 UN-No. (IATA) : 1993

14.2. Proper Shipping Name - Addition

Proper Shipping Name (ADG) : FLAMMABLE LIQUID, N.O.S. (Toleune, Acetone)
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S. (Toleune, Acetone)
Proper Shipping Name (IATA) : Flammable liquid, n.o.s. (Toleune, Acetone)

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

14.3. Transport hazard class(es)

ADG

Transport hazard class(es) (ADG) : 3
Danger labels (ADG) : 3



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3



14.4. Packing group

Packing group (ADG) : II - substances presenting medium danger

Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Marine pollutant : No Dangerous for the environment : No

Other information : No supplementary information available.

14.6. Special precautions for user

Specific storage requirement : No data available Shock sensitivity : No data available

14.7. Additional information

Other information : No supplementary information available.

Special transport precautions : Do not handle until all safety precautions have been read and understood.

Transport by road and rail

UN-No. (ADG) : 1993 Special provision (ADG) : 274 Limited quantities (ADG) : 11

Packing instructions (ADG) : P001, IBC02

Portable tank and bulk container instructions (ADG) : T7

Portable tank and bulk container special provisions : TP1, TP8, TP28

(ADG)

Transport by sea

UN-No. (IMDG) : 1993

Air transport

UN-No. (IATA) : 1993

Safety Data Sheet

according to the Model Work Health and Safety Regulations dated January 1, 2021

14.8. Hazchem or Emergency Action Code

Hazchem Code : * 3YE

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

No additional information available

15.2. International agreements

No additional information available

SECTION 16: Other information

Revision date : 29/10/2021 Expiry date : 29/10/2026 Other information : None.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



Classification	
Flam. Liq. 2	H225
Acute Tox. 4 (Oral)	H302
Acute Tox. 4 (Dermal)	H312
Acute Tox. 4 (Inhalation:vapour)	H332
Skin Irrit. 2	H315
Eye Irrit. 2A	H319
Repr. 1A	H360
STOT SE 1	H370
STOT SE 3	H336
STOT RE 2	H373
Asp. Tox. 1	H304

Safety Data Sheet (SDS), Australia - Nexreg 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.